

## Specifications

|                     |  |
|---------------------|--|
| Interior dimensions | 15.0" x 10.5" x 6.2"<br>381 mm x 267 mm x 157 mm |
| Exterior dimensions | 16.7" x 13.4" x 6.8"<br>424 mm x 340 mm x 173 mm |
| Weight (empty)      | 5.1 lb   2.3 kg                                  |
| Volume              | 16 L   |
| Temperature Range   | Mini -67°F (-55°C)<br>Max 158°F (70°C)           |
| Max Buoyancy        | 40.7 lb   18.5 kg                                |



## Available Colors



In addition to the fact that NANUK-R cases are designed for long-term use and recyclability, the shell of the NANUK-R Collection is made from a minimum of 95% post-consumer recycled resin.



| UPC Code     | Item Number    | Description                           |
|--------------|----------------|---------------------------------------|
| 666365110794 | 920SR000BK-0A0 | Nanuk-R 920 Collection - Black        |
| 666365112811 | 920SR010BK-0A0 | Nanuk-R 920 Collection w/foam - Black |

### CERTIFICATIONS



**DEF-STAN 81-41  
STANAG 4280**

*Dry Heat / Low temp  
Vibration / Water spray-rain  
Impact-Drop*



**MIL-STD-810H**

*High temp / Low temp  
Water Spray-Rain / Immersion  
Vibration / Transit Drop*



**IP67**

*Dustproof  
Immersion*



**Specifications  
ATA 300**

*Category 1  
Impact Test*



**LIFETIME  
WARRANTY**



**MILITARY  
APPROVED**



**CRUSHPROOF  
RESIN**



**RECYCLED  
RESIN**

